



REFRIGERATED COUNTERS **AURA**

AURA & AURA PIU

Experience the perfect balance of performance, durability, and smart innovation with Aura & Aura Piu Series Refrigerated Counters.

Engineered with high-density insulation and food-safe stainless steel, it ensures maximum cooling efficiency while maintaining the highest hygiene standards.

Designed for modern kitchens, it features an intelligent control system, robust construction, and an integrated airflow solution that guarantees consistent temperature distribution and optimal freshness at all times. Whether for demanding daily operations or long-term reliability, it delivers powerful performance with sleek design—making it the ideal choice for professional Kitchens

Applications: Work Top -Pizza Top – Sandwich Top-Salad Top





AURA

CFC-Free High-Density Insulation

- Polyurethane Insulation — Eco-Friendly Foam Insulation Ensures Stable Internal Temperatures And Reduced Energy Consumption.



Optional Double Drawer Modules

- Available Per Section As An Alternative To Doors, Offering Faster Access To Ingredients During Busy Service.



AISI 304 Stainless Steel Construction

- Premium-Grade Interior And Exterior Finish Delivers Maximum Durability And Compliance With The Highest Commercial Hygiene Standards.



Smart Controller

- Smart Digital Temperature Management With Precise, Real-Time Monitoring And Adjustment. Serial Port To Connect With Remote Monitoring System.



Integrated Door System

- Barrel-Locked Doors. 115° Door Dwell.



Heavy-Duty Magnetic Gasket

- Heavy-Duty Removable Magnetic Balloon Gasket For 100% Tight Seal And Easy Replacement.



Enhanced PVC Thermal Break

- Manufactured From PVC Material For Maximum Hygiene, And Fitted With A Magnetic Strip That Couples With The Door To Ensure A Complete, Airtight Seal.



Modular Heavy-Duty Shelves

- Heavy Duty, Nylon Coated Shelves.
- Anti-Tilt Tray Slides.
- Removable Racking.

AURA PIU



Intelligent Controller

- HACCP Compatible Intelligent Controller
- WiFi Connection To Platform
- Bluetooth Option To Connect



Monoblock Cooling Unit

- Fully integrated refrigeration system in a compact footprint, eliminating external components and Maximize Internal Storage



Easy-Access Service Panel

- Designed For Quick Technician Access To The Cooling Unit, Reducing Service Time And Kitchen Disruption



Full length Ergonomic Door Handle

- Smooth, Contoured Handle Designed For High-Frequency Operation In Fast-Paced Kitchen Environments



Optional R290 Eco Friendly Refrigerant

- Low Carbon Footprint | Natural Hydrocarbon | Refrigerant Which Has | Low Energy Consumption.



Front Ventilation System

- Air Intake And Exhaust Are Both Front-Facing, Allowing The Unit To Be Fully Built-In To Enclosed Cabinetry — Even In The Hottest Kitchen Environments, Operating Reliably Up To 43°C Ambient.



Round Interior Corners

- Seamless, Crevice-Free Internal Design Prevents Bacterial Accumulation And Enables Fast, Effective Daily Cleaning.



Work Preparation Top

	AURA		AURA PIU	
Model	ZC2HWT A	ZC3HWT A	ZC2HWTAP	ZC3HWTAP
Dimension	123 x 70 x 85 CM	168 x 70 x 85 CM	123 x 70 x 85 CM	168 x 70 x 85 CM
Capacity (liters)	290	450	290	450
No. of Doors	2	3	2	3
Temp C	+2/+8	+2/+8	+2/+8	+2/+8
Absorbed current	3A	3.5A	3A	3.5A
Supply Voltage	~230V/50HZ	~230V/50HZ	~230V/50HZ	~230V/50HZ
Refrigerant	R134A (R290-Optional)	R134A (R290- Optional)	R134A (R290- Optional)	R134A (R290- Optional)



Pizza Preparation Top

	AURA		AURA PIU	
Model	ZC2HPIA	ZC3HPIA	ZC2HPIAP	ZC3HSLAP
Dimension	123 x 70 x 85 CM	168 x 70 x 85 CM	123 x 70 x 85 CM	168 x 70 x 85 CM
Capacity (liters)	290	450	290	450
No. of Doors	2	3	2	3
Temp C	+2/+8	+2/+8	+2/+8	+2/+8
Absorbed current	3A	3.5A	3A	3.5A
GN	5 GN1/6	8GN1/6	5 GN1/6	8GN1/6
Supply Voltage	~230V/50HZ	~230V/50HZ	~230V/50HZ	~230V/50HZ
Refrigerant	R134A (R290-Optional)	R134A (R290- Optional)	R134A (R290- Optional)	R134A (R290- Optional)

Sandwich Preparation Top



	AURA		AURA PIU	
Model	ZC2HSNA	ZC3HSNA	ZC2HSNAP	ZC3HSNAP
Dimension	123 x 70 x 85 CM	168 x 70 x 85 CM	123 x 70 x 85 CM	168 x 70 x 85 CM
Capacity (liters)	290	450	290	450
No. of Doors	2	3	2	3
Temp C	+2/+8	+2/+8	+2/+8	+2/+8
Absorbed current	3A	3.5A	3A	3.5A
GN	5 GN1/6	8GN1/6	5 GN1/6	8GN1/6
Supply Voltage	~230V/50HZ	~230V/50HZ	~230V/50HZ	~230V/50HZ
Refrigerant	R134A (R290-Optional)	R134A (R290- Optional)	R134A (R290- Optional)	R134A (R290- Optional)



Salad Preparation Top

	AURA		AURA PIU	
Model	ZC2HSLA	ZC3HSLA	ZC2HSLAP	ZC3HSLAP
Dimension	123 x 70 x 85 CM	168 x 70 x 85 CM	123 x 70 x 85 CM	168 x 70 x 85 CM
Capacity (liters)	290	450	290	450
No. of Doors	2	3	2	3
Temp C	+2/+8	+2/+8	+2/+8	+2/+8
Absorbed current	3A	3.5A	3A	3.5A
GN	5 GN1/6	8GN1/6	5 GN1/6	8GN1/6
Supply Voltage	~230V/50HZ	~230V/50HZ	~230V/50HZ	~230V/50HZ
Refrigerant	R134A (R290-Optional)	R134A (R290- Optional)	R134A (R290- Optional)	R134A (R290- Optional)



ZETAM
THE VALUE THE QUALITY

www.zetam-professional.com
www.virtuvinox.com

ZETAM reserves the right to change dimensions, specifications, and design at anytime without prior notice



ZETAM Refrigerators